


Rainwater Harvesting System







4 Steps of Modern Rain Water Harvesting System

- Filtration of Water by Down pipe filter / Vortex filter along with the oxygen enrichment.
- Acceleration of sedimentation & distribution of oxygenated rainwater within the storage or open well.
- · Extraction of filtered water from the storage by a floating filter
- Overflow control, skimming of floating substances.

STEP-1

Down Pipe Filters For Vertical Pipes

For Roof Sizes upto 1200 sq.ft (111 sq. meter)

Easy to install

The Filter collectors are completely made of stainless-Steel, Ideal for domestic installations.



FILTER COLLECTOR (FS)

Height : 352 mm
Diameter : 120 mm
Pipe Size : 90 to 100 mm
Capacity : 3.3 liter/sec
Mesh Size : 0.28 mm
0.44 mm




Vortex Fine Filter For Horizontal Pipes

WFF 100 / WFF 150

For Roof Sizes upto 2152/5382 sq.ft (200/500 sq.meter)

Carrying capacity of vehicles upto 30 tons. Adjustable directions for inlet and outlet.





FINE FILTER WFF 100

Height : 483 mm
Diameter : 315 mm
Pipe Size : 110 mm
Capacity : 4.2 liter/sec
Mesh Size : 0.28 mm
0.44 mm



FINE FILTER WFF 150

Height : 782 mm

Diameter : 315 mm

Pipe Size : 150 /110 mm

Capacity : 12.8 liter/sec

Mesh Size : 0.28 mm

0.44 mm

WFF 300

For Roof Sizes upto 32291 sq.ft (3000 sq.meter)

Available with steel cover for underground installation to carry vehicles upto 60tons. Direction of inlet & outlet can easily be adjusted. Turnable 360 degrees.

FINE FILTER WFF 300

Height : 1020 mm
Diameter : 727 mm
Pipe Size : 300/200 mm
Capacity : 80.6 liter/sec
Mesh Size : 0.38 mm



STEP-3 STEP-4

Smoothing Inlet

- Distribution of the fresh water in upward direction
- Keeps old sediment undisturbed
- Spreads the oxygen from fresh water in the tank

SMOOTHING INLET





Floating Suction Filters

Extraction from Tanks

The floating filters extracts water from the cleanest area of the storage tank which is about 15cm below the top surface. All light weight particles float on top, all heavy particles fall to the bottom.




Multi - Siphon

For a Clean water surface & to protect water quality

- Multifunctional overflow unit.
- Made of impact-resistant ABS plastic.
- Connects to an overflow pipe.
- Remove Surface debris
- No drain smells
- Prevents rodents from entering into the tank
- Optional anti-backflow device
- · Optional anti-vermin device
- Horizontal opening maximizes skimming



Did you know that with the right technology, harvested rainwater can be made safe for drinking and cooking?



References:



Google Headquarters, New York



University of Kuala Lumpur, Malaysia



Cardiff Bus Car Wash, Wales, UK



House of German Business, Berlin, Germany



Eiffel Palace Budapest, Hungary



Maracana Olympic Stadium, Brazil, South America



Rockwell Business Center Manila, Philippines



St. Paul Saints Baseball Stadium, Minnesota, USA



Sumida City Hall, Tokyo, Japan



Under flowering elms, Recklinghausen, Germany



Levine Science Research Center, Duke University, North Carolina, USA



Carnegie Mellon University, Pittsburgh, Pennsylvania, USA



SKM Egg Products, Erode, India



TATA COMMUNICATIONS, White field, Bangalore



IKEA Rothenburg, Switzerland



RPV Enterprises

- L-330, Periyar Nagar, Erode Tamil Nadu - 638 009.
- info@rpventerprises.com
- info@rpvwisy.in
- www.rpventerprises.com
- www.wisy-water.com
- +91 81223 00301, +91 81223 00303