



RainCollector RS

Clear rainwater for your house and garden

- Including filter insert with 0.28 mm mesh size
- Automatic separation of dirt particles
- For installation in vertical pipes
- 10 years guarantee
- Easy access to the filter insert
- Drainage safety in accordance with DIN EN 752, DIN EN 12056. Complies with DIN 1989.
- Extremely low maintenance
- Oxygen enrichment of filtered water




WISY Rainwater Harvesting



The filter insert: This element is the heart of the RainCollector RS. It is completely made of stainless steel and has a mesh size of only 0,28 mm. Dirt is automatically washed away, therefore it is to a large extend self cleaning.

The blind insert: This accessory provides a direct flow of the rainwater from the roof into the drain. It is exchanged for the filter insert if the cistern is not to receive any filter water (e.g. for maintenance work).



Connecting hose or DN 50 HT tube for connecting the RainCollector RS to the rainwater barrel are also available in different colours.



WISY AG
D-63699 Kefenrod, Oberdorfstraße 26
Telefon +49 (0) 60 54-91 21-0

Construction and Mode of Operation

- The RainCatcher RC is made of UV-resistant polypropylene, suitable for tropical sunlight.
- The RainCollector RS filters the roof run-off water directly in the rainwater downpipe and then passes the filtered water through the outlet connection to the storage tank. The special construction of the filter is designed to separate coarse materials like leaves, moss, insects, etc. as well as fine pollutants which are washed through the downpipe to the soakaway or drain.
- With a mesh size of 0.28 mm the unit can supply water suitable for washing machines, WC etc. No further filtering of the water is required.
- The construction of the RainCollector RS unit creates no obstruction or narrowing of the downpipe. The Gentle Gravity Filtering technology (patented) ensures that the full flow of the rainwater in the downpipe and through the filter is maintained. This is especially important in the case of heavy rainfall. In average rainfall, over 90% of the run-off rainwater will be collected. Even in heavy downpours over 50% of the flow is filtered and collected.
- The RainCollector RS has an inlet diameter directly fitting for 110 mm round pipes. Smaller or square downpipes must be adapted to round pipes of 110 mm diameter. If the pipe diameter has been increased from a smaller diameter to 110mm, a length of at least 50cm of 110mm round pipe shall be above the filter.
- The RainCollector RS is built according to DIN and EN standards.

Field of Application

The RainCollector is designed to be inserted directly into the vertical section of a rainwater downpipe.

The most ideal collecting surfaces are pitched roofs of tiles or slate. Turf roofs are less suitable due to their low water yield. Asbestos or heavily soiled roofs should not be used.

Quality

The components are manufactured using the latest production techniques and are required to undergo the most rigorous quality control to ensure trouble-free operation. In the unlikely occurrence that parts do prove defective, WISY will guarantee replacement for 10 years.

Application example: The RainCollector RS installed in the rainwater downpipe and connected to the Stabilix rainwater barrel (500 or 750 litre) via a WISY connecting hose.



Fax +49 (0) 60 54-91 21-29
Internet: www.wisy.de
E-Mail: info@wisy.de